



#### NATIONAL ELECTRICAL and COMMUNICATIONS ASSOCIATION

## Dark Knight Engineering ELECTRICAL SAFE WORK METHOD STATEMENTS

#### TABLE OF CONTENTS - ELECTRICAL WORK

NO LIVE WORK POLICY2	3010 CONDUIT INSTALLATION, PLACED PRIOR TO POURING CONCRETE	
JOB PREPARATION INSTRUCTION3	3020 CONDUIT INSTALLATION IN THE GROUND	28
PRE-START INSPECTION AND RISK ASSESSMENT – HRA4	3040 CABLE AND LADDER TRAY INSTALLATION	30
SWMS INSTRUCTION6	3060 INSTALLATION OF SWITCHBOARDS	31
HIGH RISK CONSTRUCTION WORK7	3090 INSTALLATION OF CABLE SUPPORTS	33
2020 USING PORTABLE LADDERS8	3110 INSTALLATION OF MAINS	35
2030 MANUAL HANDLING9	3120 INSTALLATION OF SWITCHBOARD CONNECTIONS	37
2040 WORKING WITH ELEVATING WORK PLATFORMS13	3130 NEW WORK IN EXISTING SWITCHBOARDS	39
2050 ERECTING AND USING MOBILE SCAFFOLDS14	3140 INSTALLATION OF SUBMAINS	41
2060 DISMANTLING MOBILE SCAFFOLDS15	3150 INSTALLATION OF POWER AND LIGHT CABLING	43
2070 ISOLATE, LOCKOUT, TAG AND TEST16	3170 ISOLATE, LOCKOUT, TAG AND TEST	44
2080 WORKING AT HEIGHTS EWP / TOP OF ROOF PANEL18	3210 DISCONNECTING EXISTING INSTALLATION	46
2090 TESTING AND TAGGING OF ELECTRICAL APPLIANCES19	3220 TEST FOR DE-ENERGISED (DEAD)	47
2100 USE OF MOBILE PLANT21	3230 ENERGISE AND COMMISSION INSTALLATION	49
2140 CUTTING EXISTING CONDUITS23	NOTES TO CONTROL MEASURES	51
2150 HEAT SHRINK CABLE JOINTS AND LUGS25	SWMSs CONSULTATION / INSTRUCTION / TRAINING RECORD	52

- The above table lists the contents of this document. The policy, procedures and processes of these documents are the subject of induction training and an ongoing schedule of toolbox talks. A universal training and acceptance sign-off is provided on the last page.
- These SWMSs meet or exceed the requirements of the model WHS Act and Regulations for Construction and Electrical Work.

Refer revisions, comments and suggestions for improvements regarding the SWMSs to Rod Griebe at Dark Knight Engineering <a href="mailto:rod.griebe@dkegroup.com.au">rod.griebe@dkegroup.com.au</a>

The National Electrical and Communications Association, its employees, officers and agents do not accept any liability for the results of any action taken in reliance upon, based on or in connection with these proforma Safe Work Method Statements. To the extent legally possible, the National Electrical and Communications Association, its employees, officers and agents disclaim all liability arising by any breach of any duty in tort (including negligent mis-statement) or as a result of any errors or omissions contained in this document

#### NO LIVE WORK POLICY

**Dark Knight Engineering** is committed to the health, safety and welfare of our workers and others that may be affected by our work. Inadvertent contact of the body or conductive components with energised conductors or components can cause electrical shock and arcing and could result in serious injury or death. Our objective is to eliminate the probability of any such occurrence.

It is incumbent on all electrical workers to know the status of electrical conductors for the purpose of faultfinding, commissioning and testing and to ensure that contact with energised conductors does not occur. For the vast majority of other circumstances there is a prohibition on working on energised electrical equipment. Specific activities that can be justified under legislation are:

- (a) it is necessary in the interests of health and safety that the electrical work is carried out on the equipment while the equipment is energised, (e.g. hospitals) or
- (b) it is necessary that the electrical equipment to be worked on is energised in order for the work to be carried out properly, (e.g. faultfinding and commissioning) or
- (c) it is necessary for the purposes of testing to determine the status of energisation, or
- (d) there is no reasonable alternative means of carrying out the work.

This policy is explained to every electrical worker under our control. It is a requirement of this organisation that all electrical work is carried out using a safe system of work. The safe system of work must meet legislative requirements listed in a safe work procedure and checklist for energised work.

In undertaking normal electrical work, precautions must include:

#### • ONLY SUITABLY QUALIFIED

Low voltage installation work may only be undertaken by a licensed electrician, an apprentice or trainee under the supervision of a licensed electrician, or trades assistant under the direct supervision of a licensed electrician. AND

#### FOLLOW ISOLATION PROCEDURES

The circuits and apparatus of that part of the installation being worked on must not be energised, wherever practical, AND

#### ISOLATE WHERE PRACTICAL AND SHIELD EXPOSED CONDUCTORS IN THE SURROUNDING AREA

Measures to eliminate or control the risk of persons carrying out the work inadvertently contacting any part of the installation that remains energised. Any exposed conductor in the work area should be confirmed by each worker as isolated and/or securely shielded from possible contact, AND

#### TEST EVERY TIME BEFORE YOU TOUCH

Checks to ensure that the circuits and apparatus of the part of the installation that is being worked on are not energised before work commences and remain that way until the work is completed.

#### • EACH HIGH VOLTAGE EXPOSED PART IS EARTHED

Bond each phase and the neutral to earth.

The exception to these requirements is work carried out by or on behalf of an electricity supply authority, which must be undertaken under the rule governing that authority.

Note that apprentices and trainees are not permitted under any circumstances to work on live equipment, other than faultfinding, commissioning and testing.

All workers are authorised and expected to stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.

Never assume an exposed conductor is dead - test every time before you touch.

All workers must adhere to this policy to ensure their safety in the workplace. Any breach in adhering to this policy may result in immediate dismissal.

### PRE-START INSPECTION AND RISK ASSESSMENT AND SAFE WORK METHOD STATEMENTS JOB PREPARATION INSTRUCTION

- ✓ The site specific Pre-Start Inspection and the Hazard Identification and Risk Assessment form (HRA) is designed to be completed prior to commencing work on both small and large jobs.
- ✓ The HRA will be revised whenever work safety environment/conditions change or from learning following an incident and other improvements.
- ✓ The HRA forms part of the SWMSs and the HRA identifies all site-specific issues. Temporary changes or amendments to the SWMSs can become obscure. Site specific Control Measures are more readily identified in the HRA and can be communicated to workers in a more efficient and effective manner.
- ✓ The objective is zero harm.

#### **WORK ACTIVITY PLANNING:**

- Review the SWMS templates at an organisational level and with the relevant workers by way of consultation, training and participation.

  Ensure that selected Control Measures are as high as possible within the hierarchy of control eliminate risk where possible or otherwise minimise to a tolerable level.
- Approve changes to SWMS at senior management level and ensures that all workers sign prior to use.
- Carry a copy of all SWMS in each vehicle so they are available for use at every job. Have multiple copies of the HRA for use on each job.

#### PRE-START INSPECTION AND RISK ASSESSMENT:

- Carry out a Pre-start inspection and HRA on the job site. The HRA may take other forms and might be revised through the various stages of the project.
- Identify and review the appropriate Safe Work Method Statements (SWMSs) for the job and ensure that all hazards relevant to this job (or job stage) are addressed.
- Mark up any changes to the Job Steps, Potential Hazards, Risk Class and Control Measures appropriate to the job.

#### **WORKER CONSULTATION AND INVOLVEMENT:**

 Review the HRA and SWMSs with workers and all sign (HRA Sheet2/Toolbox Talk) to confirm understanding and commitment to implement the Control Measures required to carry out the work safely. Typically there is a sign-off of both the HRA and SWMSs (Sheet 3) but this can take other forms.

#### **ELECTRICAL SITE SUPERVISOR APPROVAL:**

- Any changes resulting from the Toolbox Talk (or otherwise) should be approved by the Electrical Site Supervisor and communicated with the workers and any other trades before the work commences (or continues).
- Ensure that the Safe Work documentation is available for use as required on the worksite.
- Obtain Principle Contractor representative sign-off, where required.

#### RISK MATRIX for Pre-Start Inspection and HRA/JSA:

Note: The full risk assessment is provided on the following 2 pages.

					CONSEQUENCE		
Risk Matrix		Fatality / permanent disability, off-site pollutant release causing severe environmental damage, huge financial and reputation loss	Major injury (lost time injury or illness likely), significant property damage, loss of production capability, off-site pollutant release causing major environmental damage, major financial and reputation loss	Medical treatment, major property damage, off-site pollutant release causing moderate environmental damage, moderate financial and reputation loss	First aid treatment, minor property damage, on-site release of pollutant is immediately contained, minor financial and reputation loss	Discomfort, no injuries, no environmental damage, no financial or reputation loss	
LIVELULOOD			Α	В	С	D	E
LIKELIHOOD			Critical	Major	Moderate	Minor	Insignificant
Expected to occur in most circumstance (occurs at least once a week)	1	Almost Certain	1	1	1	2	2
Will probably occur in most circumstances (occurs once or twice every month)	2	Likely	1	1	2	2	3
Should occur at some time (occurs 1 to 10 times a year)	3	Possible	1	2	2	3	3
Could occur at some time (occurs once every 2 to 10 yrs, 10% chance of occurring every year)	4	Unlikely	2	2	3	3	3
May occur only in exceptional circumstances (occurs once every 11 to 100 yrs, 1% chance of occurring every year)	5	Rare	2	3	3	3	4
LEVEL 1, HIGH RISK Unacceptable level of risk, controls must be immediately implemented to reduce risk or the risk eliminated (i.e. cease activity).  LEVEL 2, MEDIUM RISK Undesirable level of risk, additional controls must be developed and implemented in short to medium terms  Tolerable region, further controls to be considered and existing controls monitored.  Acceptable region, but current controls to be monitored (minimal risk does not mean no risk).							

<b>DARK</b> KNIGHT ENGINEERING	1	<b>ABN</b> : 7762619499	HRA Sheet 1			
9 Wenban Place, Wetherill Park, 2164	Wetherill Park, 2164 Site Supervisor/WHS Rep: Rod			Rod Griebe 0407 696 885		
Client	Project		Section	Issue Date		Prepared By
			Electrical		Rod Grieb	oe .

#### PRE-START INSPECTION AND RISK ASSESSMENT - HRA

				Risk Level (likelihood and severity): 1 = High, 2	= Medium, 3 = l	_ow, 4 =	Minimal		
Job s	stage description:				Start date:	/			
Refe	r to inspection checklist below, NEC	CA Red Book, applicable SWMSs	and releva	ant legislation, codes, standards and procedures.					
	Job tasks	Identify hazards and risks	Risk Control Measures / SWMS						
1.									
2.									
3.									
4.									
5.									
J				s appropriate for these activities on this worksite.			,		
J				. Consult with other trades / workers in the work area.					
J	J The customer understands that, whilst live work is restricted, it is generally necessary to test the installation and equipment whilst energised.								
	√ Safety observer for testing not required. Appropriate energised testing is critical to ensure that electrical workers are aware of the status of energisation.								
• T	est for de-energised every time befo	ore you touch any exposed conduc	tors						
• T	he identified Control Measure/s are	designed to eliminate the risk (whe	rever poss	sible) or otherwise minimise to an acceptable level.					

- The persons responsible for ensuring the risk Control Measures are in place are the electrical supervisor / worker doing the job.
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- This HRA is supported by the relevant SWMS, SDS, Codes, NECA Red Book and other information.

Pre-Start Preparation and Site Inspection check (Below are some areas to consider – not required to be marked)

Authority has been given to proceed with works	J	Location of nearest first aid kit is known	J	Safety equipment check	J
Others in the area are aware of the works	J	Location of fire extinguishers known	J	Test equipment check	J
Hot Work Permit completed	J	Emergency exit routes known, clear and well lit	J	Hand tools (and power tools) check	J
Confined spaces certification required	J	Barricades and signage are in-place	J	Ladders check	J
Precautions for working near water are in place	J	Alarm and/or detection isolations completed	J	Electrical leads and tools tagged, connected to RCD	J
Necessary Material Safety Data Sheets (SDS) are on site	J	Scaffolding or platforms secure and clear, edge	J	Weather, wet, sun, wind, temp., dust, noise	J
and chemicals labeled and stored correctly		protection in place.		Excessive hot or cold	
Lockout kit and Danger Tags	J	Work area adequately ventilated and well lit	J	Relevant legislation, codes, standards and client spec	J
Documentation and information available	J	Work area and access clear, tidy and dry	J	PCBs or Asbestos, SMFs, etc materials	J
Work near live exposed conductors, cabling or equipment	J	Those doing the work are inducted	J	Clean-up and rubbish disposal plan	J
Manual Handling	J				

<b>ABN:</b> 77626194992					HRA Sheet 2	
9 Wenban Place, Wetherill Park, 2164 Site Supervisor/WHS Rep			Rod Griebe 0407 6	96 885		
Client		Project	Section	Issue Date	Prepared By	
			Electrical		Rod Grieb	pe

#### PRE-START INSPECTION AND RISK ASSESSMENT - HRA

#### **WORKER SIGNOFF**

#### Worker consultation, instruction, training, toolbox talks, review, acceptance record:

I, the undersigned, acknowledge, that:

- 1. I have been consulted regarding the content of the PRE-START INSPECTION AND RISK ASSESSMENT (HRA), SWMSs and the NECA Red Book,
- 2. the relevant hazards, control measures, rules and requirements have been explained to me and are clearly understood by me,
- 3. I have read, understand and accept, this HRA and documents referenced in the control measures, including "No Live Work Policy", SWMSs and Red Book, and I, the undersigned, acknowledge, understand and accept that:
  - 1. I shall only carry out work for which I am trained, instructed, equipped and competent,
  - 2. I have advised my supervisor of any individual needs in relation to carrying out the work safely,
  - 3. I will comply with the HRA, "No Live Work Policy" and SWMSs, otherwise work must stop immediately,
  - 4. I will be vigilant regarding hazards and the suitability of the HRA and SWMS for the task at hand and implement further control measures where required, and
  - 5. I understand that I am authorised and expected to safely stop work and immediately notify my supervisor if a task carries an unacceptable level of risk.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					
2					
3					
4					
5					
6					
7					
8					
9					

ABN: 77626194992						
9 Wenban Place, Wetherill Park, 2164 Site Superv		or/WHS Rep:	Rod Griebe 04	107 696 885		· ·
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

### SWMS INSTRUCTION SAFE WORK METHOD STATEMENTS

These Safe Work Method Statements have been developed in consultation with the NECA Safety Committee and are reviewed to suit the organisation's safe work practices, and are designed as an instruction for persons carrying out the work.

The format is a MS Word table and is based on the requirements for SWMSs for Construction (WHS model Regulations Chapter 6 and Code of Practice) and Electrical (WHS Part 4.7 and Code of Practice).

The Risk Levels in the Safe Work Method Statements are defined as follows:

Level 1, High Risk: Does the hazard have the potential to kill or permanently or temporarily disable?

Level 2, Medium Risk: Does the hazard have the potential to cause lost time injury or illness?

Level 3, Low Risk: Does the hazard have the potential to cause a minor injury that might require first aid?

Level 4, Minimal Risk: Work activity is not expected cause harm, subject of appropriate implementation of risk control measures.

- The identified Control Measure/s are designed to eliminate the risk (wherever possible) or otherwise minimise to a tolerable level.
- The persons responsible for ensuring the risk Control Measures are in place are the electrical supervisor / worker doing the job.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Critically, and in conjunction with the HRA, the SWMS communicates to the person/s doing the work appropriate Control Measures for the specific task step.

#### **EVALUATION AND REVIEW PROCESS:**

- Review each of the SWMSs and edit to suit your general operations and/or specific projects. Prepare additional SWMS for other work processes that you undertake.
- Print out a copy for each work vehicle, file along with a copy of the NECA Red Book, so that a reference copy is available to the worksite.
- Review and evaluation of SWMSs is an ongoing process and is undertaken formally as a routine, at least annually.
- SWMS/HRA are formally reviewed & updated whenever:
  - ✓ a significant change to task or activity is identified
  - ✓ an incident occurs relating to the task or activity
  - ✓ a significant hazard is identified relating to the task or activity or
  - ✓ periodically as required.

Copies of NSW legislation are available from www.legislation.nsw.gov.au.

Copies of WHS model Codes of Practice and guidelines are available from <u>safeworkaustralia.gov.au/</u> or your local regulator.

Australian Standards may be acquired from <u>www.saiglobal.com</u> or from NECA offices

Copies of the NECA Red Book 2007 are available from NECA and reputable electrical wholesalers.

The NECA website is at www.neca.asn.au

For further information or to make suggestions or provide input for developing additional Safe Work Method Statements, please contact Dark Knight Engineering rod.griebe@dkegroup.com.au

ABN: 77626194992					
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Re	Rod Griebe 0	407 696 885		· ·
Client	Project	Section	Issue Date	App	proved by
		Electrical		Rod Griebe	

#### HIGH RISK CONSTRUCTION WORK

These Safe Work Method Statements (SWMS) have been prepared as per the model Work Health and Safety Regulation 2011 (Part 4.7 – Electrical and Chapter 6 - Construction Work [see Regulation 161(3) and 299]) which:

• identifies the work that is high risk construction work (HR-ID: 1 to 18):

HR-ID	Types of High Risk Construction Work
1	Involves a risk of a person falling more than 2 metres
2	Is carried out on a telecommunication tower
3	Involves demolition of an element of a structure that is load-bearing or otherwise related to the physical integrity of the structure
4	Involves, or is likely to involve, the disturbance of asbestos
5	Involves structural alterations or repairs that require temporary support to prevent collapse
6	Is carried out in or near a confined space
7	Is carried out in or near:
	<ul> <li>a shaft or trench with an excavated depth greater than 1.5 metres, or</li> </ul>
	a tunnel
8	Involve the use of explosives
9	Is carried out on or near pressurised gas distribution mains or piping
10	Is carried out on or near chemical, fuel or refrigerant lines
11	Is carried out on or near energised electrical installations or services
12	Is carried out in an area that may have a contaminated or flammable atmosphere
13	Involves tilt-up or precast concrete
14	Is carried out on, in or adjacent to a road, railway, shipping lane or other traffic corridor that is in use by traffic other than pedestrians
15	Is carried out in an area at a workplace in which there is any movement of powered mobile plant
16	Is carried out in an area in which there are artificial extremes of temperature
17	Is carried out in or near water or other liquid that involves a risk of drowning
18	Involves diving work

- specifies hazards relating to the high risk construction work and risks to health and safety associated with the identified hazards
- describes the measures to be implemented to control the risks
- describes how the control measures are to be implemented, monitored and reviewed.

Note: these SWMS exceed the requirements of the WHS Regulations and Code of Practice - Construction Work

For construction jobs where the principal requires SWMS under WHS Chapter 6, only those rows that are identified with a HR-ID number from the above table need be presented. All other row addressing non high risk work may be deleted. It is recommended that workers in our industry work to the full document.

ABN: 77626194992						
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS R	Rep: Rod Griebe 04	107 696 885		J	
Client	Project	Section	Issue Date	App	roved by	
		Electrical		Rod Griebe		

	2020 USING PORTABLE LADDERS									
Distribution:	□ Client (WHS rep)	□ Company Personnel								
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)						

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Select appropriate ladder with regard to compliance with the relevant part of AS 1892 and the work to be done.	Electric shock  Manual handling	1 2	Metal or wire reinforced ladders shall not be used for any electrical work working near electricity Ensure adequate lighting Use correct technique and seek assistance as required	4	Electrical Supervisor / Worker doing the job	11
3	Inspect the ladder for condition.	Falling	2	Inspect ladders. Do not use damaged ladders.	4	Electrical Supervisor / Worker doing the job	1
4	Position ladder to ensure stability.	Falling	1	Position ladders a minimum of 1 metre from edges of slabs or floors Increase this distance as working heights increases. Straight or extension ladders to be secured at top and bottom Ladders need to extend 1 metre above landing level and to be long enough to work at least 1 metre from the top Angle of ladder should be nominally 1 in 4	4	Electrical Supervisor / Worker doing the job	1
5	Ascending or descending a ladder	Falling	1	Maintain three points of contact on the ladder Never tread on the top three rungs.	4	Electrical Supervisor / Worker doing the job	1
6	Working from ladder	Falling	1	Wear bump hat with chinstrap in place for prolonged work. Retain three points of contact at all times. Always face the ladder and keep inside styles. Never tread on the top three rungs. Fall protection to be used when working above 1.8m Refer SWMS2080	4	Electrical Supervisor / Worker doing the job	1

ZOKE B B DARK KNIGHT ENGINEERING			ABN: 776261	Page 9 of 52			
9 Wenban Place, Wetherill Park, 2164	Site Supervise	or/WHS Rep:	Rod Griebe 0407 696 885			3	
Client		Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe		
	0000 1		NIDLINIO				

# Distribution: ☐ Client (WHS rep) ☐ Company Personnel Risk Level: ☐ HIGH (Death, permanent disability) ☐ Center (Major injury, lost time injury/illness) ☐ Center (Major injury) ☐ Center (Major inju

,	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record)	Site specific issues Worker safety Public access and	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage	4 4 4	Electrical Supervisor / Worker doing the job	
	and secure area	unauthorised persons	3	Observe No live work policy	4		
2	For simple manual handling tasks and activities	Musculoskeletal injury and disorders	2	Limit lifting loads to manageable levels (refer Appendix 1 for info) Follow steps below but without preparing job specific forms	4	Electrical Supervisor / Worker doing the job	
3	Identify characteristics:			Use National Code of Practice: Hazardous Manual Tasks (2011) Follow manual handling and lifting rules Involve employees in preparation			
4	The object to be handled.	Sizes, shapes, weight, bulk, stability, hot, cold, sharp edges grip.	2	Complete Risk Identification as in Appendix 1	4	Electrical Supervisor / Worker doing the job	
5	The task.	Frequency, bending, reaching, twisting, balance, distances, forces.	2	Complete Risk Identification as in Appendix 1.	4	Electrical Supervisor / Worker doing the job	
6	The working environment	Space, access, lighting, floor surfaces, hot/cold.	2	Complete Risk Identification as in Appendix 1.	4	Electrical Supervisor / Worker doing the job	
7	The individuals involved.	New, ages, disabilities, PPE & C, training, hazard awareness. If team lifting, training and physically matched	2	Complete Risk Identification as in Appendix 1.	4	Electrical Supervisor / Worker doing the job	
8	Assess characteristics of:						
9	The working area.  Heights, space, chair lighting, floors, and access.		2	Complete Risk Identification as in Appendix 2 Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
1 0	The people.  Sufficient, new, ages, disabilities, PPE & C, training, hazard awareness. If team lifting, training and physically matched.		2	Complete Risk Identification as in Appendix 2.	4	Electrical Supervisor / Worker doing the job	

ZOKE B B DARK KNIGHT ENGINEERING		<b>ABN</b> : 776261	94992			Page 10 of 52
9 Wenban Place, Wetherill Park, 2164	Site Superviso	Site Supervisor/WHS Rep: Rod Griebe 0407 696 885				3.
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

,	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	The actions of people.	Posture, bending, stretching, reaching, twisting, and handling techniques.	2	Complete Risk Identification as in Appendix 2.	4	Electrical Supervisor / Worker doing the job	
1 2	The object.	Size, shape, weight, bulk, stability, hot, cold, sharp edges, grip, accurate placement.	2	Complete Risk Identification as in Appendix 2.	4	Electrical Supervisor / Worker doing the job	
1	Control hazards using the Hierarchy of Control and measures developed from 1 and 2.	Personal injuries and property damage.	2	Formulate action plans to include (1.5) What is to be done, Who will be responsible for completion, When will the work be completed, and Monitoring and reviewing the outcomes.	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DARK KHIGHT ENGINEERING		<b>ABN</b> : 77626194992				
9 Wenban Place, Wetherill Park, 2164	Site Supervis	or/WHS Rep:	Rod Griebe 04			
Client	Project		Section	Issue Date	Ap	proved by
			Electrical		Rod Griebe	

#### Appendix 1 - Manual Handling Risk Identification Checklist

No.		Yes	No	No.		Yes	No
Post	ure and Layout			11	Is the weight of the object:- a) more than 4.5 kg and handled from a seated position		
1	Is stooping involved where the hands pass below mid thigh height? See risk factors 1 & 2				b) more than 16-20 kg and handled in a working posture other than seated		
2	Is reaching above shoulder height involved?  See risk factors 1 & 2				c) more than 55 kg See risk factor 6		
3	Is forward reaching (more than 30cm from the body) involved? See risk factors 1 & 2			12	Does the object have sharp edges or contain hot or cold materials?  See risk factor 7		
4	Is significant sideways twisting of the body involved?  See risk factors 1 & 2			13	Does it have unstable or unbalanced contents?  See risk factor 7		
5					Are live persons or animals that may move around being moved?  See risk factor 7		
6	Is an awkward grip involved?  See risk factor 7			15	Are slippery materials or objects being handled? See risk factor 7		
Task	and Object			16	Is the object bulky or awkward to handle e.g. more than 75 cm in two dimensions? See risk factor 7		
7	Is handling performed for more than one hour at a time? See risk factors 3 & 4			Work	place Conditions		
8	Is handling performed more than once every five minutes?  See risk factors 3 & 4			17	Is the task being performed in a confined or cramped space? See risk factor 8		
9	Are there any forces applied to move the object, apart from lifting e.g. pushing, pulling, restraining, holding?  See risk factor 5			18	Is the workplace where the task is to be performed hot, cold or poorly lit e.g. furnace / coolroom?  See risk factor 8		
10	Is there a long vertical distance of travel (more than 25cm)?  See risk factor 4			19	Are the floor surfaces slippery, sloped or uneven? See risk factor 8		

DARK KNIGHT ENGINEERING		ABN: 77626		Page 12 of 52			
9 Wenban Place, Wetherill Park, 2164	Site Superv	Supervisor/WHS Rep: Rod Griebe 0407 696 885					
Client	Project		Section	Issue Date	App	proved by	
			Electrical		Rod Griebe		

#### Appendix 2 - Manual Handling Hazard Identification and Controls Worksheet

		Control C	Options						
Risk Fa	actors								
		Modify Object	Modify Workplace Layout	Rearrange Materials Flow	Different Actions, Movements	Modify Task Mechanical Assistance	Modify Task Team Lifting	Mechanical Handling Equipment	Particular Training
1	Actions and Movements Used								
2	Posture and Layout								
3	Duration and Frequency								
4	Time and Distance								
5	Force Applied								
6	Weight								
7	Nature of Object Load								
8	Condition of Workplace Environment								
Consid	er further factors such a	as the follo	wing			·			
9	Work Organisation								
10	Age								
11	Skill and Experience								
12	Mechanical Aids Available								

DAR	DKE 8				<b>ABN</b> : 776261	94992				<b>Page 13 of</b> 52		
9	Wenban Place, Wetherill	Park, 2164		Site Supervis	or/WHS Rep:	Rod Griebe 04	ebe 0407 696 885			J		
	Clier	nt		Project Section Sectio			Issue Date		Appr	roved by		
				Electrical						Rod Griebe		
		20	MODI	KING WITH ELEVATIN	IC WORK BL	ATEODMS						
Di	istribution:	Client (WHS rep)			NG WORK PL	ATFURING						
		th, permanent disability)		Company Personnel 2 = MEDIUM (Major injury, lost time injury/illness) 3 = LOW (First aid, no lost time) 4 =							njuries)	
	,				<u>j</u> aj,		•			1= (	.juee,	
	Work Method Description (in steps)	Possible hazards and risks	Risk Level	(	Control measures	S		Post Risk	Responsik	ole Person	HR-ID	
1	Undertake / confirm	Site specific issues		Do inspection and review task				4	Electrical S			
	workplace risk assessment	Worker safety		Check test equipment and PPI				4	Worker doi:	ng the job		
	HRA (document record) and secure area	Public access and unauthorised persons		Clear area and use appropriat Observe No live work policy	e barricades and s	signage		4				
2	Check that machine is safe	Machine failure, personal			gbook, hydraulics, tyres, audible alarm, and warning lights  4 Electrical Superior						15	
	to use mechanically.	injury		Involve employees in preparat	ion				Worker doi:	ng the job		
3	Check electrical equipment	Electric shock		Check socket outlet, Post curr		rth continuity bet	ween earth	4	Electrical S		11	
	on machine.	B.A. 1.2 1 (1.12)		pin and machine frame. Trip to		1 20 0		4	Worker doi:		4.5	
4	Check surfaces on which the machine is to be used.	Machine instability		Use machine only on stable, level surfaces in accordance with the manufacturer's instructions					Electrical S Worker doi		15	
5	Secure working area.	Personal injuries		Barricade working area, erect signs, tie tools on, and secure objects left at					Electrical S			
Ĭ	3	, ,		height					Worker doi:			
	D ((	D 1:::		Ensure adequate lighting				4	FI .: 10		4	
6	Prevent falls.	Personal injuries		Use parachute harness with la Ensure attachment point is app		absorber		4	Electrical S Worker doi		1	
				Stay wholly within the bucket a					Worker don	ing the job		
				Enter or exit bucket only while								
				Use the machine only in wind	less than 12.5 m/s	ec						
7	Check services in work area.	Personal injuries	2	Isolate as required				4	Electrical S Worker doi		11	
									Worker doll	ing the job		
•	Test for de-energised ever				to and in fit for m							
	All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose All workers to be vigilant in relation of changes in safety conditions and workplace environment.											
•				d immediately notify their su		carries an una	cceptable level	of risk	ζ.			
•				monitored and reviewed by								
	ead, understood, accepted ar				t 3 at back of doc							
#	SURNAME	GIVEN NAME		ROLE SIGNATURE					DATE			
1												

DAF	RE KNICHT ENGINEERING				<b>ABN</b> : 776261	94992				Page 14	<b>of</b> 52	
9	Wenban Place, Wetherill	Park, 2164		Site Supervis	or/WHS Rep:	Rod Griebe	ebe 0407 696 885					
	Clier	nt		Project			Issue Date		Аррі	oved by	oved by	
				-		Electrical		Ro	Rod Griebe			
								1.0	u 011000			
			2050 ER	RECTING AND USING N	MOBILE SCA	FFOLDS						
D		Client (WHS rep)		Company Personnel								
R	Risk Level: 1 = HIGH (Dear	th, permanent disability)	2 = ME	EDIUM (Major injury, lost time	e injury/illness)	3 = LOW (	First aid, no lost	time)	4 = MIN	IMAL (no ir	njuries)	
	Work Method Description	Possible hazards and	Risk		Control measures	s		Post	Responsik	ole Person	HR-ID	
	(in steps)	risks	Level	6		1 1 1 1 1		Risk	-		וווי-וט	
1	Undertake / confirm workplace risk assessment	Site specific issues Worker safety	3 3	Do inspection and review tasks Check test equipment and PPI				4	Electrical S Worker doi			
	HRA (document record)	Public access and	3	Clear area and use appropriate				4	Worker don	ig the job		
	and secure area	unauthorised persons		Observe No live work policy	o barrioadoo aria e	ngriago						
2	Erect scaffold in	Unstable ground	2	Place appropriate sole boards				4	Electrical S			
	accordance with the	Overturning		Involve employees in preparati	ion				Worker doi	ng the job		
	manufacturer's or supplier's	Collapse										
	instructions.	Falling	1	Ensure handrails are fitted as				1				
3	Proximity to wires	Electric shock	1	Use fall protection as appropria				4	Electrical S	upor icor /	11	
3	Proximity to wires	Electric shock	1	Shield all exposed conductors		iuciois		4	Worker doi		11	
4	Check surfaces on which	Scaffold instability	2	Use scaffold only on stable, level surfaces in accordance with the					Electrical S		1	
•	the scaffold is to be used.		_	manufacturer's instructions					Worker doi		·	
5	Secure working area.	Personal injuries	2	Barricade working area, erect	signs, tie tools on,	and secure of	jects left at	4	Electrical S		1	
				height					Worker doi	ng the job		
				Ensure adequate lighting								
				Wear appropriate personal pro Stay wholly within the scaffold		I						
6	Observe safe work	Personal injuries	2	Use appropriate fall protection.		hserved and v	vheels are	4	Electrical S	unervisor /	1	
0	procedures for erection and	1 Oroonal Injunios		locked when in working position			TIOOIS AIG		Worker doi			
	use			Use the scaffold only in wind le		ес				,		
		Manual handling	2	Use correct technique and see	k assistance as re	equired		4				
7		Personal injuries	1	Isolate as required				4	Electrical S		11	
	area.								Worker doi	ng the job		
•	Test for de-energised ever	y time before you touch a	ny expose	d conductors								
•	•											
•				itions and workplace environr								
•				nd immediately notify their su					ζ.			
•				d monitored and reviewed by			as a result of ch	ange.				
#		GIVEN NAME		efer to universal signoff Sheet ROLE	3 at Dack of doc		NATURE			DATE		
1	JUNIVAIVIE	GIVEN NAME		NOLL		310	MATURE			DAIL		

2 DARK	CKNIGHT ENGINEERING					<b>ABN</b> : 776261	94992			Page 15	of 52	
9	Wenban Place, Wetherill	Park, 2164			Site Superviso	or/WHS Rep:	Rod Griebe 0	407 696 885			0.02	
	Clie	nt			Project	Section Issue Date				Approved by		
							Electrical		Rod Griebe			
2060 DISMANTLING MOBILE SCAFFOLDS												
		Client (WHS_rep)		mpany Personn								
Ri	tisk Level: 1 = HIGH (Death, permanent disability) 2 = MEDIUM (Major injury, lost time injury/illness) 3 = LOW (First aid, no lost time) 4 = MINIMAL (no injuries)											
Work Method Description (in steps)  Possible hazards and risks  Risk Level  Control measures						Post Risk	Responsible Person	HR-ID				
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy					4 4 4	Electrical Supervisor / Worker doing the job		
2	Clear area of extraneous materials	Falling objects	2	Ensure work plan Involve employe		ior to dismantling			4	Electrical Supervisor / Worker doing the job		
3	Dismantle scaffold in accordance with the manufacturer's or supplier's instructions.	Electric shock Overturning Personal injury Manual handling	1 2 2 2	Remove lower tie Wear appropriate Ensure ropes for	es only when the e personal prote r lowering equipr	ained from conduct e scaffold is disma ctive equipment ment are securely assistance as req	antled down to the tied.	nat level.	4 4 4	Electrical Supervisor / Worker doing the job	11	
4	Secure working area.	Personal injury	2	Barricade workir	ng area and erec	t signs			4	Electrical Supervisor / Worker doing the job		
•	All PPE and test equipmer All workers to be vigilant i All workers are authorised	ry time before you touch are it shall be inspected prior to in relation of changes in sa I and expected to safely sto in consultation with the wo	o use, to fety con op work	o ensure it is safe ditions and work and immediately	cplace environn notify their su	nent. pervisor if a task	carries an una			ς.		
	ead, understood, accepted a			•	I signoff Sheet	3 at back of doc						
#	SURNAME	GIVEN NAME		ROLE			SIGN	ATURE		DATE		

DARK KNICHT ENGINEERING	ABN: 776261	ABN: 77626194992				
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	sor/WHS Rep: Rod Griebe 0407 696 885				
Client	Project	Section	Issue Date	App	proved by	
		Electrical		Rod Griebe		

		2070 ISOLATE, LOCKOUT, TAG AND T	EST	
Distribution:	□ Client (WHS rep)	□ Company Personnel		
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Notify occupiers / tenants of potential power outages		N/A	Protect against unauthorised access.	N/A		
3	Identify ALL energy sources to be isolated (8.2).	Electric Shock Personal injury	1	Do not work live Use appropriate PPE designed for electrical testing Involve workers in preparation Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	11
4	Confirm and record phase rotation if required for commissioning purposes prior to de-energising.	Electric Shock	1	Use appropriate PPE designed for electrical testing	4	Electrical Supervisor / Worker doing the job	11
5	Isolate ALL power sources associated with the works to be carried out as per site requirements and install insulating barriers.	Electric Shock	1	Switch power off and rack-out or remove removable breakers Observe a safe work distance of 500mm from exposed conductors Ensure other power sources where inadvertent contact could occur in the course of work to be conducted are also isolated Check that auxiliary circuits are not energised (e.g. emergency services)	4	Electrical Supervisor / Worker doing the job	11
6	Secure the isolation.	Electric Shock	1	Lockout and danger tag relevant circuit breakers Use lockout hasp for multiple padlocks Alternatively remove and tie back and tag connections	4	Electrical Supervisor / Worker doing the job	11
7	Bond conductors where safe and practicable	Electric Shock	1	Test first for dead and equipotential Use heavy duty clips and wire – connect to earth/neutral wire first	4	Electrical Supervisor / Worker doing the job	11
8	Fit DANGER TAGS to isolation devices.	N/A	N/A	Sign, date and include warning of any abnormal hazard	N/A		
9	Test that work area has been safely isolated/deenergised (i.e. DEAD) using appropriate test device.	Electric Shock	1	Confirm de-energisation before commencing work Check exposed conductors in work area to 500mm of body/tool reach Follow Standard Working Procedures TEST EVERY TIME BEFORE YOU TOUCH	4	Electrical Supervisor / Worker doing the job	11

ZOKE B B DARK KNIGHT ENGINEERING		ABN: 77626194992					
9 Wenban Place, Wetherill Park, 2164	Site Superv	ervisor/WHS Rep: Rod Griebe 0407 696 885				Page 17 of 52	
Client			Section	Issue Date	App	proved by	
			Electrical		Rod Griebe		

	Work Method Description (in steps) Possible hazards and risks		Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake scope of work to client's specifications.	Electric Shock	1	Follow appropriate SWMSs and HRAs Work to AS/NZS 3000 and/or other specified or relevant standards TEST EVERY TIME BEFORE YOU TOUCH	4	Electrical Supervisor / Worker doing the job	11
1	Make safe prior to leaving site.	Electric Shock	1	Fit Out of Service/ Danger Tags to any incomplete work Ensure that installation cannot be energised by switch	4	Electrical Supervisor / Worker doing the job	11
1 2	Commission and make safe prior to re-energising.	Electric Shock	1	Ensure safe - follow swms3230	4	Electrical Supervisor / Worker doing the job	11

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DARK KNIGHT ENGINEERING		ABN: 77626	194992	Page 18 of 52		
9 Wenban Place, Wetherill Park, 2164	Site Supervi	sor/WHS Rep:	or/WHS Rep: Rod Griebe 0407 696 885			
Client			Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

## 2080 WORKING AT HEIGHTS EWP / TOP OF ROOF PANEL Distribution: □ Client (WHS rep) □ Company Personnel Risk Level: 1 = HIGH (Death, permanent disability) 2 = MEDIUM (Major injury, lost time injury/illness) 3 = LOW (First aid, no lost time) 4 = MINIMAL (no injuries)

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures Po		Responsible Person	HR-ID
	Undertake / confirm workplace risk assessment HRA (document record) and secure area  Working at heights can be in the form of:  Working on a roof panel  on the top of a tank  from an EWP  working within 2.0 m of an edge where there is the potential to fall 2.0 m or more.	Site specific issues Worker safety Public access and unauthorised persons Falling Personal injury	3 3 3 1 2	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy Involve employees in preparation Ensure adequate lighting Recommended controls for fall protection can be in three forms or a combination of either  1. Fall prevention – placing a physical barrier to prevent personnel working where they can fall e.g.:  Fixed barricading set back 3.0m from any fall potential 2. Fall restraint – limiting personnel from reaching the point of potential fall, e.g.:  Roofing kneel boards to spread the load over a span Anchorage points must be in place prior to commencement of work.  Personnel must be attached, via lanyard, prior to any exposure to risk of fall  Elevating Work Platform - Only personnel trained and certificated to operate this equipment.	4 4 4 4	Electrical Supervisor / Worker doing the job  Electrical Supervisor / Worker doing the job	1
•	Emergency rescue	Hanging	1	Where there is a risk of fall, persons are not to work alone.  Personnel should be trained in fall-arrest and rescue	4	Electrical Supervisor / Worker doing the job	1

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

DABK KNIGHT ENCINEERING		ABN: 776261	194992	<b>Page 19 of</b> 52		
9 Wenban Place, Wetherill Park, 2164	Site Supervis	sor/WHS Rep: Rod Griebe 0407 696 885				
Client Project			Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

## Distribution: □ Client (WHS rep) □ Company Personnel Risk Level: □ 1 = HIGH (Death, permanent disability) □ Company Personnel □ Company Personne

,	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Ensure that work complies with AS3760 and to Clause 64 and 65 of the NSW WHS Regulation 2011 Check operation of test equipment.  Unplug equipment from the  Inadequate knowledge Overlook fault  Person undertaking work must be competent Refer to codes and standard Involve employees in preparation Ensure adequate lighting  Switch off at socket and disconnect plug		4	Electrical Supervisor / Worker doing the job	11		
3	Unplug equipment from the supply.	Electric shock	1	Switch off at socket and disconnect plug	4	Electrical Supervisor / Worker doing the job	11
4	Undertake visual and physical inspection for damage and defects in appliance, accessories, connectors, plugs and extension outlet sockets.	Minor cuts from sharp edges	3	Apply due care in inspection Wear PPE where appropriate	4	Electrical Supervisor / Worker doing the job	
5	Check flexible cords are effectively anchored to equipment, plugs and sockets.	Hand injuries and cuts	3	Apply due care in inspection Wear PPE where appropriate	4	Electrical Supervisor / Worker doing the job	
6	Test earth continuity resistance not exceeding 1 ohm.	Hand injuries and cuts	3	Apply due care in inspection Wear PPE where appropriate	4	Electrical Supervisor / Worker doing the job	
7	Test insulation resistance not less than 1 megohm.	Hand injuries and cuts	3	Apply due care in inspection Wear PPE where appropriate	4	Electrical Supervisor / Worker doing the job	
8	Alternatively use leakage current test at rated voltage Class I – 5mA max Cords and Class II – 1mA max	Electric shock Note the protective earth conductor may be live whilst testing	1	Protect equipment with RCD or isolating transformer.  Refer to stringent precautions to be followed when doing live testing in the COP Managing electrical risks in the workplace and prepare a separate risk assessment and SWMS for this work	4	Electrical Supervisor / Worker doing the job	11

<b>2</b> KE B B B B B B B B B B B B B B B B B B			<b>ABN</b> : 776261	94992	Page 20 of 52			
9 Wenban Place, Wetherill Park, 2164	S	ite Superviso	risor/WHS Rep: Rod Griebe 0407 696 885					
Client		Project		Section	Issue Date	App	proved by	
				Electrical		Rod Griebe		

,	Work Method Description Possible hazard (in steps) risks		Risk Level		Post Risk	Responsible Person	HR-ID
9	Prepare and fit tag to compliant equipment. Complete equipment log / register as a record and provide client with copy.	N/A	N/A	Tags do not have to be colour coded.	N/A		
1 0	Take faulty items out of service and advise client of issue so client can arrange repair / replacement	N/A	N/A	N/A	N/A		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DARK KNICHT ENGINEERING	ABN: 776261	<b>ABN</b> : 77626194992				
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	isor/WHS Rep: Rod Griebe 0407 696 885			Page 21 of 52	
Client	Project	Section	Issue Date	App	proved by	
		Electrical		Rod Griebe		

	2100 USE OF MOBILE PLANT								
Distribution:	□ Client (WHS rep)	□ Company Personnel							
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)					

V	Vork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Verify location of current services prior to bulk excavation (gas, power, telephone, water, sewer) and tree roots	Electric shock	1	Dial 1100 before you dig where appropriate [5.3] – i.e. breaking the ground Locate services by non invasive digging and moved outside excavation area Identify overhead power lines and maintain safe approach distances	4	Electrical Supervisor / Worker doing the job	11
3	Confirm plant and equipment inspection / maintenance checks have be undertaken where appropriate (Mobile plant daily check report)	Equipment moving	2	Ensure plant is immobilised All mobile plant to be fitted with audio alarm (motion and reverse) All mobile plant to be fitted with amber flashing light Safe weight limit to be displayed on plant / arm or stamped on equipment	4	Electrical Supervisor / Worker doing the job	15
4	Prevent unauthorised use of plant	Injury and damage	2	Render plant immobile whilst not in attendance Do not leave keys in unattended plant Only drive if you have the appropriate licence and or certificate of competency	4	Electrical Supervisor / Worker doing the job	15
5	Spotter	Person or property being hit	2	A spotter may be used in areas that may prevent the operator visibility is limited or operator control measures are difficult Spotter to wear high visibility clothing, eye protection and helmet (to suit) Spotter must be in continuous contact with operator by hand signals or radio	4	Electrical Supervisor / Worker doing the job	15
6	Plant operation	Person or property being hit	1	Trenching refer to swms2110 Ensure adequate lighting Personnel in area to wear hi-vis clothing Plant to stop if person or property (overhead wires) is in danger of being hit No person to approach mobile plant until confirmed contact is made with the operator either by hand signals or radio Payload to face uphill when moving up or down a slope	4	Electrical Supervisor / Worker doing the job	15
		Plant becoming unstable	1	Consider one way plant movement to reduce vehicle accidents Ensure secure footing and stable ground on paths of travel Observe strict slope, reach and load limits	4		15

ZOKE B B DARK KNIGHT ENGINEERING		<b>ABN</b> : 77626194992					
9 Wenban Place, Wetherill Park, 2164		Site Supervisor/WHS Rep: Rod Griebe 0407 696 88		407 696 885		Page 22 of 52	
Client	Project		Section	Issue Date	Арј	proved by	
			Electrical		Rod Griebe		

Work Method Description (in steps)  Possible hazards and risks		Risk Level	CONTROL MASSILING	Post Risk	Responsible Person	HR-ID
7 Refuelling of machinery	Fire and explosion  Manual handling	2	Shut down plant and ensure no open flames and no smoking in area Ensure fire extinguisher is available and keep bystanders clear Remove static electricity potentials - touch the fuel can and the plant away from the nozzle Do not overfill, and avoid spillage and excessive vapours Use correct technique and seek assistance as required	4	Electrical Supervisor / Worker doing the job	10 12

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DARK KNIGHT ENGINEERING	ABN: 776261	<b>ABN</b> : 77626194992				
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	rvisor/WHS Rep: Rod Griebe 0407 696 885			_ Page 23 of 52	
Client	Project	Section	Issue Date	App	proved by	
		Electrical		Rod Griebe		

	2140 CUTTING EXISTING CONDUITS								
Distribution:	☐ Client (WHS rep)	□ Company Personnel							
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)					

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm	Site specific issues	3	Do inspection and review tasks and review HRA checklist	4	Electrical Supervisor /	
	workplace risk assessment	Worker safety	3	Check test equipment and PPE, consult with workers involved	4	Worker doing the job	
	HRA (document record)	Public access and	3	Clear area and use appropriate barricades and signage	4		
	and secure area	unauthorised persons		Observe No live work policy			
2		Trips, slips and falls	3	Check for steep or slippery surfaces and obstructions	4	Electrical Supervisor /	1
	potential power outages			Ensure adequate lighting at work site		Worker doing the job	
				If conduit is already in service take particular care in cutting process			
3	,	Electric shock	1	Assume energised until positive tests confirms de-energised	4	Electrical Supervisor /	11
	wiring/cables in the			Test before you touch		Worker doing the job	
	conduit by tracing to and		_	Ensure that all cables in the conduit are accounted for			4.4
	checking the starting and	Some cabling may come	1	Be aware of main, auxiliary and alternative sources of supply	4		11
	end points of the conduit	from other power sources i.e. mixed circuits in the		If conduit could be associated with network or other supply, confirm authorisations			
	Review available  drawings visual	one conduit		Be aware of possibility of concealed J-boxes			
	drawings, visual inspection and	Cuts and abrasions		Wear protective clothing and gloves if necessary	4		
	verification	Manual handling	3	Use correct technique and seek assistance as required	4		
	Use physical	Maridar Hariding	2	Ose correct technique and seek assistance as required	7		
	tracing where		_				
	practicable						
_	Progressively isolate	The switchboard could	1	Undertake isolation procedure	4	Electrical Supervisor /	11
	relevant circuits	still have power	-			Worker doing the job	
F	Confirm point of cut and	Cuts	2	Wear gloves and eye protection if necessary	4	Electrical Supervisor /	
`	make accessible		_	graves and eye processor,		Worker doing the job	
6	Cut the conduit	Electric shock	1	Use insulated mat and wear gloves and eye protection as necessary	4	Electrical Supervisor /	11
	<ul> <li>Ring the conduit</li> </ul>					Worker doing the job	
	at partial						
	thickness by						
	using a plumbers						
	pipe cutter and						
	snap						
7		Electric shock	1	Use insulated mat and wear gloves and eye protection as necessary	4	Electrical Supervisor /	11
	makeup of exposed cables					Worker doing the job	

DARK KNIGHT ENGINEERING		ABN: 77626194992					Page 24	<b>of</b> 52		
9 Wenban Place, Wetherill Park, 2164			Site Supervisor/WHS Rep: Rod Griebe 04		407 696 885					
Client			Project		Section	Issue Date	App		proved by	
				Electrical Rod Griebe		d Griebe				
Work Method Description (in steps)	Possible hazards and risks	Risk Level		Control measure	·s		Post Risk	Responsib	le Person	HR-ID

Work Method Description (in steps)	Possible hazards and risks	Risk Level	('Antrol mageurae	Post Risk	Responsible Person	HR-ID
8 Continue safe work procedure		N/A	Refer relevant SWMS and HRA Restore installation to appropriate safety and wiring standards before restoring power	N/A		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ABN: 77626194992					
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	Rod Griebe 0407 696 885			Page 25 of 52
Client	Project	Section	Issue Date	App	proved by
		Electrical		Rod Griebe	

		2150 HEAT SHRINK CABLE JOINTS AND	LUGS	
Distribution:	□ Client (WHS rep)	□ Company Personnel		
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Clean cable sheath to remove any oil, grease, water, dirt etc by wiping the cable ends and connector/link  Remove any sharp edges or burrs	Chemical irritants	3	Refer to SDS and follow safe work practices set out therein	4	Electrical Supervisor / Worker doing the job	10 12
3	Select tube, boot, cap size to suit cable size  • When waterproofing use adhesive lined where possible and allow twice minimum seal length	N/A	N/A		N/A		
4	Cut tube to length and fit to cable	Cut injury	3	Use side cutter where practical Wear protective gloves where appropriate	4	Electrical Supervisor / Worker doing the job	
5	Crimp conductor connection or lug and centre the tubing over the splice connectors/links	Hand injuries Hand injuries	3	Use appropriate tool to crimp lug / sleeves Use tools correctly	4	Electrical Supervisor / Worker doing the job	

DARK KNIGHT ENGINEERING		<b>ABN</b> : 77626	194992			Page 26 of 52
9 Wenban Place, Wetherill Park, 2164		upervisor/WHS Rep:	Rod Griebe 0407 696 885			3
Client	Proje	ot	Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

'	Nork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
6	Apply broad gentle heat evenly to all sides of heat shrink material  Larger heat shrink materials require use of flame  Start at centre and work to one end first  If using a gas burner, use the cooler, soft flame  Do not hold the torch still in one position or concentrate the hot inner flame of the torch on the tubing; this may cause scorching  Keep the heat source moving around the circumference of the insulator to ensure uniform shrinkage Installation is complete when the tubing conforms to the link and if present, adhesive flow is apparent at both ends	Burns and fire	2	Use heat gun where possible to avoid open flame Complete site hot work permit if using open flame Ensure fire extinguisher is available when using open flame Check for flammable substances (including gas) before using open flame Use shield / reflector to protect other areas and get uniform heat coverage Do not touch the heat shrink product until it cools Ensure no one inadvertently touches hot parts of heating gun/torch after use	4	Electrical Supervisor / Worker doing the job	10 12
7	Tidy up	Fire, contaminants	2	Spent butane / gas canisters contain residual fuel and should not puncture or disposed in general rubbish	4	Electrical Supervisor / Worker doing the job	10 12

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

<b>DARK KNIGHT ENCINEERING</b>		<b>ABN</b> : 776261	94992			<b>Page 27 of</b> 52
9 Wenban Place, Wetherill Park, 2164			3			
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	
<u>.                                    </u>			•		•	

	3010 CONDUIT INSTALLATION, PLACED PRIOR TO POURING CONCRETE							
Distribution:	□ Client (WHS rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record)	Site specific issues Worker safety Public access and	3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage	4 4	Electrical Supervisor / Worker doing the job	
2	and secure area Check layout and mark out.	unauthorised persons Tripping and exposed	3	Observe No live work policy  Ensure areas in particular walkways are clear	4	Electrical Supervisor /	
	-	nails		·	<u> </u>	Worker doing the job	
3	Install disposable lids for conduit boxes to timber	Cuts and abrasions	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
4	Lay conduit and accessories.	Chemical glues Manual handling	3 2	Refer to SDS and follow safe work practices set out therein Use correct technique and seek assistance as required	4 4	Electrical Supervisor / Worker doing the job	10
5	Tie down conduit	Cuts and abrasions	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

  Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ABN: 77626194992							
9 Wenban Place, Wetherill Park, 2164	Site Supervis	sor/WHS Rep: Rod Griebe 0407 696 885				J	
Client	Project		Section	Issue Date	App	proved by	
			Electrical		Rod Griebe		

	3020 CONDUIT INSTALLATION IN THE GROUND									
Distribution:		Client (WHS_rep)	□ Company Personnel							
Risk Level:	1 = HIGH (Death	n, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)					

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
•	Undertake / confirm	Site specific issues	3	Do inspection and review tasks and review HRA checklist	4	Electrical Supervisor /	
	workplace risk assessment	Worker safety	3	Check test equipment and PPE, consult with workers involved	4	Worker doing the job	
	HRA (document record)	Public access and	3	Clear area and use appropriate barricades and signage	4		
	and secure area	unauthorised persons		Observe No live work policy			
1	Minimise impact on public	Public safety	2	Schedule earthwork outside periods of high use (e.g. school hours (or use	4	Electrical Supervisor /	14
	and persons in the area			school holidays)) as much as possible		Worker doing the job	
(	Check area for other	Sun exposure	2	Use skin protection	4	Electrical Supervisor /	
	services and confirm	Tripping	3	Ensure area is clear	4	Worker doing the job	
	locations of any gas lines,			Ensure location of other services is confirmed and appropriate access permits			
	power cables, telephone			obtained.			
	cables, water or sewer lines	Underground services	2	Dial 1100 before you dig	4		9
	and tree roots.		_	DBUD Maps must be no more than 30 days old	_		
4	Check layout and mark out	Tripping	3	Ensure area is clear	4	Electrical Supervisor /	
			_	Wear safety footwear		Worker doing the job	
	Excavate trenches	Mobile plant	2	Observe safe work practices for mobile plant	4	Electrical Supervisor /	15
				Observe processes for trenching in		Worker doing the job	
		Manual handling	2	Use correct technique and seek assistance as required	4		
			•	Ensure trenches are as even and flat as practical			4
		Falling in trenches	2	Barricade work area. Delineate top of batter to prevent encroachment of	4		1
		Transk sallanas	1	mobile plant and vehicles			7
		Trench collapse	1	Provide shoring, benches or battering in accordance with WorkCover requirements	4		1
		Services damage	3	Provide warning lights if necessary overnight	4		
	Lay conduit	Fire and explosion	3	Comply WorkCover requirements	4	Electrical Supervisor /	
'	Lay conduit	Personal injury	3	Implement risk management procedures	4	Worker doing the job	
		Electric shock	1	Confirm any existing installations are dead	4	Tromer deling the jes	11
		Confined / restricted	2	Follow Standard Working Procedures	4		6
		spaces		3.13.33.33	-		
	Restore ground to client's	Manual handing	2	Use correct technique and seek assistance as required	4	Electrical Supervisor /	
	specifications	Tripping	3	Ensure area is clear	4	Worker doing the job	
		-					

ABN: 77626194992							
9 Wenban Place, Wetherill Park, 2164	Site Supervis	sor/WHS Rep: Rod Griebe 0407 696 885				•	
Client	Project		Section	Issue Date	Арј	proved by	
			Electrical		Rod Griebe		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

  Read understood accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DAF	AK KNIGHT ENGINEERING						<b>ABN</b> : 776261	94992					Page 30	of 52
9	Wenban Place, Wetherill	Park, 210	64			Site Supervis	or/WHS Rep:	Rod Grieb	Griebe 0407 696 885				· · ·	
	Clier	nt				Project		Section	n l	ssue Date	Approved		roved by	
								Electrica	al		Ro	d Griebe		
							TRAY INST	ALLATIO	N					
		Client (WF			oany Personne									
R	tisk Level: 1 = HIGH (Dea	th, permar	nent disability)	2 = MEI	DIUM (Major ir	njury, lost tim	e injury/illness)	3 = LOV	V (First a	aid, no lost	time)	4 = MIN	IIMAL (no ir	njuries)
	Work Method Description (in steps)		e hazards and risks	Risk Level		Contro	I measures * (Cla	use No.)			Post Risk	Responsil	ole Person	HR-ID
1	Undertake / confirm	Site speci	ific issues	3	Do inspection a	nd review task	s and review HRA	checklist			4	Electrical S	Supervisor /	
	workplace risk assessment	Worker sa	afety	3	Check test equi	pment and PP	E, consult with wo	rkers involve	ed		4	Worker doi		
	HRA (document record)	Public acc					e barricades and	signage			4			
2	and secure area Check layout and mark out		sed persons and exposed		Observe No live		kways are clear				4	Electrical S	upor igor /	
	Check layout and mark out	nails	ina exposea		Wear safety foo		kways are clear				4	Worker doi		
		Tidilo			Ensure adequat							Tronkor do.	ing and job	
3		Debris an	d noise from				onsistent with effec	ctive work			4	Electrical S		
	using correct size bolts and	drilling			Use PI respirato							Worker doi	ng the job	
	fixings				Use appropriate Ensure drill bits		n							
4	Cut ladders or trays to fit	Noise ev	e injuries, cuts		Ensure work pie						4	Electrical S	Supervisor /	
-	using drop saw or 100mm	and abras					n and use gloves	if necessary	,		•	Worker doi		
	angle grinder	Manual ha		2	Use correct tech	hnique and see	ek assistance as re	equired			4			
5			abrasion from		Use ladders in a			100000			4	Electrical S		
	support	sharp edg	jes		Use fall protection Use gloves if ne		opriate refer SWM	IS2080				Worker doi	ng the job	
6	Remove sharp edges and	Working a	at heights, falls		Use ladders in a		th SWMS2020				4	Electrical S	Supervisor /	1
	protruding fixings						opriate refer SWM	IS2080			·	Worker doi		·
		Manual ha	andling				ek assistance as re	equired			4			
		Duma a a	d finas fra		Follow Hot Worl		and proceedings	ro in risss						
		cutting an	d fires from d weldina	2	Ensure emerger	ncy equipment	and procedures a	ire in place			4			
	Tool for do considered according													
•	Test for de-energised ever All PPE and test equipmen					to uselonera	to and is fit for n	irnose						
	All workers to be vigilant in							ui puse						
•	All workers are authorised							carries an	unacce	ptable level	of risk	ζ.		
•	Each SWMS is developed	in consulta	ation with the wo	rkers, and	monitored and	d reviewed by	management per	riodically ar						
	ead, understood, accepted ar	nd signed l				signoff Shee	t 3 at back of doc							
#			GIVEN NAME		ROLE			S	IGNATL	JRE			DATE	
1														

ZOKE B DARK KNIGHT ENGINEERING	ABN	<b>N</b> : 7762619	94992	Page 31 of 52		
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/Wh	HS Rep:	Rod Griebe 04	107 696 885		<b>3</b>
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

	3060 INSTALLATION OF SWITCHBOARDS								
Distribution:	☐ Client (WHS rep)	□ Company Personnel							
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)					

V	Vork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Confirm installation specifications.	N/A	N/A	Involve employees in preparation  Note special requirements for temporary construction wiring	N/A		
3	Prepare installation area and confirm adequate space including door swing for maintenance.	Hand injuries, tripping and exposed nail	3	Ensure areas in particular walkways are clear Wear safety footwear Ensure adequate lighting Use suitable gloves if necessary Check for auxiliary circuits and alternative sources of supply	4	Electrical Supervisor / Worker doing the job	11
4	Arrange for crane or other mechanical handling equipment if needed.	Traffic issues	2	Provide traffic control	4	Electrical Supervisor / Worker doing the job	14
5	Receive switchboard on site including test certificates.	Falling objects Manual handling	2 2	Keep lifting area clear of people Use correct technique and seek assistance as required	4 4	Electrical Supervisor / Worker doing the job	
6	Transfer switchboards to installation location	Falling objects Manual handling	2 2	Use mechanical handling equipment Use correct technique and seek assistance as required Consider use of mobile plant	4 4	Electrical Supervisor / Worker doing the job	
7	Mark out location ensuring coordination with other services.	N/A	N/A	N/A	N/A		
8	Install switchboard to manufacturer's and client's specifications.	Manual handling Electric shock	2	Implement manual handling risk control procedures Refer SWMS2030 Ensure cables are de-energised before cutting Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
9	Commission switchboard	Electric shock, explosion	1	Carry out pre-commission test and isolation procedures	4	Electrical Supervisor / Worker doing the job	11

<b>ABN:</b> 77626194992								<b>of</b> 52
9 Wenban Place, Wetherill Park, 2164		Site Supervisor/WH	HS Rep:	Rod Griebe 0407 696 885				
Client		Project Section Issue Date Ap		proved by				
				Electrical		Rod Griebe		

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	L'ONTROL MASCURGE	Post Risk	Responsible Person	HR-ID
1 0	Clean area	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ABN: 77626194992									
9 Wenban Place, Wetherill Park, 2164			or/WHS Rep:	Rod Griebe 04	107 696 885		Page 33 of 52		
Client		Project		Section	Issue Date	App	proved by		
				Electrical		Rod Griebe			
3090 INSTALLATION OF CABLE SUPPORTS									
Distribution: ☐ Client (WHS_rep)	□ Company Personne	el							
Risk Level: 1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major in	njury, lost time	e injury/illness)	3 = LOW (Fi	rst aid, no lost ti	ime) 4 = MI	NIMAL (no injuries)		

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Check location to drawing and specifications	Tripping and exposed nails	3	Ensure area is clear Wear safety footwear Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
3	Receive cable supports on site confirming correct type, size and number	Struck by falling objects Manual handling	2 2	Keep lifting area clear of people Use correct technique and seek assistance as required	4 4	Electrical Supervisor / Worker doing the job	
4	Mark out route of cable supports to specifications confirming clearance of other services	Falling	2	Use ladders in accordance with SWMS2020 Use fall protection as appropriate	4	Electrical Supervisor / Worker doing the job	1
5	Install supports to client's specifications supporting as necessary and using correct size bolts.	Electric shock Falling	1 2	Ensure power tools and leads are tagged Use ladders in accordance with SWMS2020	4 4	Electrical Supervisor / Worker doing the job	11 1
6	Confirm tightness of fixings	Falling	2	Use ladders in accordance with SWMS2020	4	Electrical Supervisor / Worker doing the job	1
7	Install cable supports	Struck by falling objects Falling	2 2	Keep lifting area clear of people Use ladders in accordance with SWMS2020 Use fall protection as appropriate	4 4	Electrical Supervisor / Worker doing the job	1
8	Clean area	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors (swms3220).
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose (3.7, 3.8).
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

# SURNAME GIVEN NAME ROLE SIGNATURE DATE

<b>ABN</b> : 77626194992							
9 Wenban Place, Wetherill Park, 2164	Site Super	Site Supervisor/WHS Rep: Rod Griebe 0407 696 885				Page 34 of 52	
Client	Project		Section	Issue Date	App	pproved by	
			Electrical		Rod Griebe		
1							

DARK KNIGHT ENDINEERING	194992	<b>Page 35 of</b> 52				
9 Wenban Place, Wetherill Park, 2164		Supervisor/WHS Rep:	Rod Griebe 0	407 696 885		3
Client	Proj	ject	Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

	3110 INSTALLATION OF MAINS							
Distribution:	☐ Client (WHS_rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

V	Work Method Description (in steps)  Possible hazards and risks		Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Liaise with Supply Authority to coordinate supply.	N/A	N/A	N/A	N/A		
3	Obtain Supply Authority Certificates and check drawings.	N/A	N/A	N/A	N/A		
4	Coordinate shutdowns with client and workers.	N/A	N/A	Involve employees in preparation	N/A		
5	Receive mains on site.	Falling objects Manual handling	2 2	Keep lifting area clear of people Use correct technique and seek assistance as required	4 4	Electrical Supervisor / Worker doing the job	
6	Shut down and install DANGER Tags.	Electric shock	1	Isolate, lock, tag and test Check for auxiliary circuits and alternative sources of supply Confirm DEAD before commencing work	4	Electrical Supervisor / Worker doing the job	11
7	Remove existing mains terminations if applicable.	Electric shock	1	Confirm DEAD before commencing work	4	Electrical Supervisor / Worker doing the job	11
8	Install mains to specifications.	Electric shock Manual handling	1 2	Confirm DEAD before commencing work Use correct technique and seek assistance as required	4 4	Electrical Supervisor / Worker doing the job	11
9	Terminate new mains to specifications.	Electric shock	1	Confirm DEAD before commencing work	4	Electrical Supervisor / Worker doing the job	11
1 0	Confirm installation to drawings and specifications and ensure connections are tight.	Electric shock	1	Confirm DEAD and identify cables before commencing work Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
1	Clean area.	Hand injuries	3	Wear suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
1 2	Test installation.	Electric shock	1	Confirm DEAD and identify cables before commencing work Refer swms3230 - Energise and commission	4	Electrical Supervisor / Worker doing the job	11

<b>ABN:</b> 77626194992						
9 Wenban Place, Wetherill Park, 2164		Site Supervisor/WHS Rep: Rod Griebe 0407 696 885			Page 36 of 52	
Client	Project		Section	Issue Date	Арј	proved by
			Electrical		Rod Griebe	

V			Risk Level	Control measures P		Responsible Person	HR-ID
1 3	Liaise with Supply Authority for inspection and test.	N/A	N/A	N/A	N/A		
1	Remove DANGER Tags.	Incorrect procedure	3	Energise and commission	4	Electrical Supervisor / Worker doing the job	
1 5	Energise supply.	Electric shock	1	Check for exposed conductors and terminate all, prior to energising Follow Standard Working procedures.	4	Electrical Supervisor / Worker doing the job	11
1 6	Install signs or labels as required.	Hand injuries	3	Use tools appropriately	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ZOKE B B DARK KNIGHT ENGINEERING	<b>ABN</b> : 776261	ABN: 77626194992			
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	Rod Griebe 04	107 696 885		J
Client	Project	Section	Issue Date	App	proved by
		Electrical		Rod Griebe	

3120 INSTALLATION OF SWITCHBOARD CONNECTIONS								
Distribution:	☐ Client (WHS rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

	Work Method Description (in steps)  Possible hazards and risks  Risk Level  Control measures		Control measures	Post Risk	Responsible Person	HR-ID	
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Confirm switchboard meets and has been installed to specifications	N/A	N/A	Refer swms3060	N/A		
3	Confirm cables to be connected meet specifications and all cables have been installed. Check any specific requirements have been met.	Tripping and exposed nails	3	Ensure area is clear Wear safety footwear Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
4	Group cables together as they enter switchboard and fix with cable ties.	Manual handling Hand injuries	2	Use correct technique and seek assistance as required Involve employees in preparation Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
5	Separate cables into groups of like destination. Seal or plug any unused cable entries.	Electric shock	1	Confirm DEAD before commencing work	4	Electrical Supervisor / Worker doing the job	11
6	Mark each conductor prior to removing any secondary insulation.	N/A	N/A	N/A	N/A		
7	Group conductors of like destinations and fix into a loom system	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
8	Align and terminate each conductor into its correct location.	Electric shock	1	Confirm DEAD before commencing work	4	Electrical Supervisor / Worker doing the job	11
9	Check and tighten all terminations and connections.	Electric shock	1	Confirm DEAD before commencing work Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
1 0	Confirm installations meet specifications.	N/A	N/A	N/A	N/A		
1	Install labels, signs or markings as required.	N/A	N/A	N/A	N/A		

ABN: 77626194992						<b>Page 38 of</b> 52
9 Wenban Place, Wetherill Park, 2164		sor/WHS Rep:	or/WHS Rep: Rod Griebe 0407 696 885			•
Client	Project		Section	Issue Date	Ap	proved by
			Electrical		Rod Griebe	

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1 2	Clean switchboard.	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
1	Confirm all circuits have been completed and DANGER TAG any incomplete circuits.	Incorrect procedure	3	Isolation, tag and test	4	Electrical Supervisor / Worker doing the job	
1 4	Test and commission switchboard using relevant procedures. Confirm phase rotation of all 3 phase equipment.	Electric shock	1	Follow safe work practices Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
1 5	Complete records	N/A	N/A	N/A	N/A		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ZOKE Š B DARK KNICHT ENCINEERINO		<b>ABN</b> : 77626	194992			<b>Page 39 of</b> 52
9 Wenban Place, Wetherill Park, 2164	Site Superv	isor/WHS Rep:	Rod Griebe 0	407 696 885		· ·
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

	3130 NEW WORK IN EXISTING SWITCHBOARDS							
Distribution:	☐ Client	(WHS rep)	□ Company Personnel					
Risk Level:	1 = HIGH (Death, pe	manent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)			

	Work Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Check drawings and specifications.	N/A	N/A	Refer to the no live work policy Involve employees in preparation Ensure adequate lighting	N/A		
3	Arrange isolation of section of, or complete switchboard with client.	N/A	N/A	Isolate tag and test	N/A		
4	Isolate section of, or complete switchboard, install insulating barriers.	Electric shock	1	Isolate all energy sources Confirm DEAD before commencing work Check for auxiliary circuits and alternative sources of supply Follow Standard Working Procedures	4	Electrical Supervisor / Worker doing the job	11
5	Fit DANGER TAGS to isolation devices.	Incorrect procedure	3	Isolation, tag and test	4	Electrical Supervisor / Worker doing the job	
6	Test that work area has been safely isolated.	Electric shock	1	Confirm DEAD before commencing work Follow Standard Working Procedures	4	Electrical Supervisor / Worker doing the job	11
7	Complete installations to client's specification.	Electric shock  Manual handling	1 2	Test and identify cables before commencing work Check for exposed conductors and terminate all, prior to energising Use correct technique and seek assistance as required	4	Electrical Supervisor / Worker doing the job	11
8	Check and tighten all terminations and connections.	Electric shock	1	Confirm DEAD before commencing work Follow Standard Working Procedures	4	Electrical Supervisor / Worker doing the job	11
9	Confirm installation to client's specifications.	N/A	N/A	N/A	N/A		
1 0	Fit DANGER TAGS to any incomplete work.	N/A	N/A	Isolation, tag and test	N/A		
1	Install labels, signs or markings as required.	N/A	N/A	N/A	N/A		
1 2	Clean work area.	Hand injuries	3	Wear suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	

ABN: 77626194992							Page 40 of 52	
9 Wenban Place, Wetherill Park, 2164		e Superviso	sor/WHS Rep: Rod Griebe 0407 696 885					
Client	Project			Section	Issue Date	Ар	proved by	
				Electrical		Rod Griebe		

	(in steps) risks Level Control measures		Post Risk	Responsible Person	HR-ID		
1 3	Test and commission new installation following relevant procedures. Confirm phase rotation of all 3 phase equipment.	Electric shock	1	Follow Standard Working Procedures Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
1	Complete records.	N/A	N/A	N/A	N/A		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ABN: 77626194992					Page 41 of 52	
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	Rod Griebe 04	od Griebe 0407 696 885			
Client	Project Section Issue Date A		App	proved by		
		Electrical		Rod Griebe		

	3140 INSTALLATION OF SUBMAINS						
Distribution:	☐ Client (WHS_rep)	☐ Company Personnel					
Risk Level:	1 = HIGH (Death, permanent disa	bility) 2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)			

V	Vork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Check location to drawings and specification layout and mark out	Tripping and exposed nails	3	Ensure area is clear Wear safety foot wear Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
3	Plan installation so as to work towards the main switchboard.	Electric shock	1	Isolate all energy sources Connections to the main switchboard to be made ONLY when it is CONFIRMED DEAD Check for auxiliary circuits and alternative sources of supply	4	Electrical Supervisor / Worker doing the job	11
4	Confirm cable specifications and condition.	N/A	N/A	N/A	N/A		
5	Install cable to client's specifications.	Falls  Manual handling Electric shock	2 2 1	Use ladders in accordance with Use fall protection as appropriate Use correct technique and seek assistance as required Ensure that no bare conductors can contact any live parts Effectively insulate both ends of all cables near any live parts. Restrain the ends of all cables near any live parts.	4 4 4	Electrical Supervisor / Worker doing the job	11
6	Terminate sub mains to specifications.	Electric shock	1	Isolate main switchboard and install DANGER TAGS Isolation, lock, tag and test CONFIRMED DEAD before making any connections Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
7	Clean area	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
8	Test installation	Electric shock	1	CONFIRMED DEAD and identify cables before commencing work refer SWMS3220	4	Electrical Supervisor / Worker doing the job	11
9	Remove DANGER TAGS	Incorrect procedure	3	Energise and commission	4	Electrical Supervisor / Worker doing the job	

DABIK KHICHT ENGINEERING		ABN: 776261	194992			<b>Page 42 of</b> 52
9 Wenban Place, Wetherill Park, 2164		or/WHS Rep:	Rod Griebe 04	107 696 885		
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

'	Work Method Description (in steps)  Possible hazards and risks		Risk Level		Post Risk	Responsible Person	HR-ID
1	Energise main switchboard.	Electric shock	1	Follow Standard Working Procedures	4	Electrical Supervisor / Worker doing the job	11
1	Install signs or labels as required.	Hand injuries	3	Use tools appropriately Wear suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

  Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

DARK KNIGHT ENGINEERING	94992			<b>Page 43 of</b> 52		
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	Rod Griebe 04	Griebe 0407 696 885			
Client	Project Section Issue Date		App	proved by		
		Electrical		Rod Griebe		

	3150 INSTALLATION OF POWER AND LIGHT CABLING						
Distribution:		□ Client (WHS rep)	□ Company Personnel				
Risk Level:	1 = HIGH (De	eath, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)		

	Work Method Description Possible hazards a (in steps) risks		Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Check location to drawings and specification layout and mark out	Tripping and exposed nails	3	Ensure area is clear Wear safety foot wear Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
3	Plan installation so as to work towards the main switchboard.	Electric shock	1	Connections to the main switchboard to be made only when it is CONFIRMED DEAD	4	Electrical Supervisor / Worker doing the job	11
4	Confirm cable specifications and condition.	N/A	N/A	N/A	N/A		
5	Install cable to client's specifications.	Falls  Manual Handling  Electric shock	2 2 1	Use ladders in accordance with Use fall protection as appropriate Use correct technique and seek assistance as required Ensure that no bare conductors can contact any live parts Effectively insulate both ends of all cables near any live parts Restrain the ends of all cables near any live parts	4 4	Electrical Supervisor / Worker doing the job	1 11
6	Terminate submains to specifications.	Electric shock	1	Isolate main switchboard and install DANGER TAGS Isolation, tag and test CONFIRMED DEAD (swms3220) and identify cables before commencing work Check for exposed conductors and terminate all, prior to energising	4	Electrical Supervisor / Worker doing the job	11
7	Clean area	Hand injuries	3	Use suitable gloves if necessary	4	Electrical Supervisor / Worker doing the job	
8	Test installation	Electric shock	1	CONFIRMED DEAD (swms3220) and identify cables before commencing work (swms3220)	4	Electrical Supervisor / Worker doing the job	11
9	Remove DANGER TAGS	Incorrect procedure	3	Energise and commission (	4	Electrical Supervisor / Worker doing the job	
10	Energise main switchboard.	Electric shock	1	Follow Standard Working Procedures (swms3230)	4	Electrical Supervisor / Worker doing the job	11
11	Install signs or labels as required.	Hand injuries	3	Use tools appropriately	4	Electrical Supervisor / Worker doing the job	

DAKK KNIGHT ENGINEERING		ABN: 776261	94992			Page 44 of 52
9 Wenban Place, Wetherill Park, 2164 Sit		sor/WHS Rep:	Rod Griebe 04	107 696 885		
Client	Project		Section	Issue Date	Арр	proved by
			Electrical		Rod Griebe	

	3170 ISOLATE, LOCKOUT, TAG AND TEST							
Distribution:	☐ Client (WHS_rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

V	Vork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Notify occupiers / tenants of potential power outages		N/A	Protect against unauthorised access.	N/A		
3	Identify ALL energy sources to be isolated (8.2).	Electric Shock Personal injury	1	Do not work live Use appropriate PPE designed for electrical testing Involve workers in preparation Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	11
4	Confirm and record phase rotation if required for commissioning purposes prior to de-energising.	Electric Shock	1	Use appropriate PPE designed for electrical testing	4	Electrical Supervisor / Worker doing the job	11
5	Isolate ALL power sources associated with the works to be carried out as per site requirements and install insulating barriers.	Electric Shock	1	Switch power off and rack-out or remove removable breakers Observe a safe work distance of 500mm from exposed conductors Ensure other power sources where inadvertent contact could occur in the course of work to be conducted are also isolated Check that auxiliary circuits are not energised (e.g. emergency services)	4	Electrical Supervisor / Worker doing the job	11
6	Secure the isolation.	Electric Shock	1	Lockout and danger tag relevant circuit breakers Use lockout hasp for multiple padlocks Alternatively remove and tie back and tag connections	4	Electrical Supervisor / Worker doing the job	11
7	Bond conductors where safe and practicable	Electric Shock	1	Test first for dead and equipotential Use heavy duty clips and wire – connect to earth/neutral wire first	4	Electrical Supervisor / Worker doing the job	11
8	Fit DANGER TAGS to isolation devices.	N/A	N/A	Sign, date and include warning of any abnormal hazard	N/A		
9	Test that work area has been safely isolated/deenergised (i.e. DEAD) using appropriate test device.	Electric Shock	1	Confirm de-energisation before commencing work Check exposed conductors in work area to 500mm of body/tool reach Follow Standard Working Procedures TEST EVERY TIME BEFORE YOU TOUCH	4	Electrical Supervisor / Worker doing the job	11
1 0	Undertake scope of work to client's specifications.	Electric Shock	1	Follow appropriate SWMSs and HRAs Work to AS/NZS 3000 and/or other specified or relevant standards TEST EVERY TIME BEFORE YOU TOUCH	4	Electrical Supervisor / Worker doing the job	11

ABN: 77626194992						<b>Page 45 of</b> 52
9 Wenban Place, Wetherill Park, 2164		rvisor/WHS Rep:	sor/WHS Rep: Rod Griebe 0407 696 885			J
Client	Project		Section	Issue Date	Арј	proved by
			Electrical		Rod Griebe	

Work Method Description (in steps)  Possible hazards and risks		Risk Level		Post Risk	Responsible Person	HR-ID	
1	Make safe prior to leaving site.	Electric Shock	1	Fit Out of Service/ Danger Tags to any incomplete work Ensure that installation cannot be energised by switch	4	Electrical Supervisor / Worker doing the job	11
1 2	Commission and make safe prior to re-energising.	Electric Shock	1	Ensure safe - follow swms3230	4	Electrical Supervisor / Worker doing the job	11

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

  Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

	<b>DKE</b> an					770004	04000					
DA	RK KNIGHT ENGINEERING					<b>ABN</b> : 776261	94992				Page 46	<b>of</b> 52
9	9 Wenban Place, Wetherill Park, 2164			Site	Superviso	r/WHS Rep:	Rod Griebe 04	107 696 885			_	
	Clie	nt		Proje	ect		Section	Issue Date		Appro	ved by	
							Electrical		Roo	d Griebe		
		Client (WHS rep) th, permanent disability)  Possible hazards and	□ Con	ISCONNECTING  npany Personnel  EDIUM (Major injury,	, lost time		3 = LOW (Fi	rst aid, no los	Post	4 = MININ	`	njuries) HR-ID
	(in steps)	risks	Level		·	ontroi measure	:5		Risk	Responsible	Person	חול-וט
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and rev Check test equipmen Clear area and use a Observe No live work	nt and PPE appropriate	, consult with wo	rkers involved		4	Electrical Sup Worker doing		
2	Notify tenants of potential power outages		N/A	Ensure adequate ligh	nting				N/A			
3	Isolate the Work Area, test, tag and lock	The switchboard could still have power Some cabling may come	1	Undertake isolation p Clearly mark with tem		)e			4	Electrical Sup Worker doing		11 11
		from other power	•			-						

protective clothing and gloves if necessary

Check test instrument against known source

Use safe means of raising and lowering materials

Wear protective clothing and gloves if necessary

Use correct handling and lifting methods

Use safe ladder procedure

Use safe ladder procedure

Test before touch be aware of auxiliary and alternative sources of supply Wear

Use insulated tools and equipment and gloves and eye protection if necessary

Electrical Supervisor /

Worker doing the job

4

4

4

4

4

11

1

1

11

1

Test for de-energised every time before you touch any exposed conductors

sources

Electric shock

Electric shock

Falling objects

Back injury

Cuts and abrasions

Test instrument fails

Use of ladder - falls

Use of ladder – falls

Cuts and abrasions

Disconnect cabling at

5 Test for live cables in work

area and identify with

back to source, confirm

cable is dead and cut to

6 Trace individual cables

switchboard

temporary tape

remove

**7** Tidy up

• All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose

3

2

2

1

2

2

2

2

- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

Read	ead, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):								
#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE				
1									

ABN: 77626194992					Page 47 of 52	
9 Wenban Place, Wetherill Park, 2164	Site Superv	isor/WHS Rep:	Rod Griebe 0	407 696 885		· ·
Client	Project		Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

	3220 TEST FOR DE-ENERGISED (DEAD)							
Distribution:	□ Client (WHS rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

١	Vork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy (1.3)	4 4 4	Electrical Supervisor / Worker doing the job	
2	Confirm isolation of energy sources		N/A	Refer isolation section of swms3170 Observe No live work policy	N/A		
3	Select suitably rated test equipment	Internal breakdown	2	Instrument should be Cat3 or better for normal 240/415volt work	4	Electrical Supervisor / Worker doing the job	
4	Check your test device/equipment for integrity and ensure is in good working order.		N/A	Before test, prove testing equipment is working correctly Ensure adequate lighting	N/A		
5	Locate reference earth potential conductors.	Electric Shock	1	Only touch bare earth conductor with insulated instrument probe	4	Electrical Supervisor / Worker doing the job	11
6	Identify all possible relevant electrical conductors to be confirmed DEAD within 500mm of body/tool reach.	Electric Shock	1	Do not touch (other than with test probe) Be aware of auxiliary supplies for energised sources Isolate or shield exposed conductors if energised	4	Electrical Supervisor / Worker doing the job	11
7	Test that work area has been safely isolated/de-energised (i.e. DEAD) using appropriate test device.	Electric Shock	1	Only touch bare earth conductor with insulated instrument probe Confirm de-energisation and safe before commencing work Refer to 9.1 for possible additional precautions	4	Electrical Supervisor / Worker doing the job	11
8	Confirm post-test that your test device is operational.		N/A	After test, prove testing equipment is working correctly	N/A		
9	Only touch (i.e. make body contact) electrical conductors where necessary	Electric Shock	1	Reprove they are DEAD - as above before touching TEST EVERY TIME BEFORE YOU TOUCH Use insulated tools	4	Electrical Supervisor / Worker doing the job	11
1 0	Continue safe work procedure		N/A	Refer relevant SWMS and HRA	N/A		

ABN: 77626194992						Page 48 of 52
9 Wenban Place, Wetherill Park, 2164	Site Supervi	sor/WHS Rep:	Rod Griebe 04	107 696 885		J
Client	Project		Section	Issue Date	Арј	proved by
			Electrical		Rod Griebe	

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

  Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					
					l

ABN: 77626194992					
9 Wenban Place, Wetherill Park, 2164	Site Supervisor/WHS Rep:	sor/WHS Rep: Rod Griebe 0407 696 885			J
Client	Project	Section	Issue Date	App	proved by
		Electrical		Rod Griebe	

	3230 ENERGISE AND COMMISSION INSTALLATION							
Distribution:	□ Client (WHS rep)	□ Company Personnel						
Risk Level:	1 = HIGH (Death, permanent disability)	2 = MEDIUM (Major injury, lost time injury/illness)	3 = LOW (First aid, no lost time)	4 = MINIMAL (no injuries)				

\	Nork Method Description (in steps)	Possible hazards and risks	Risk Level	Control measures	Post Risk	Responsible Person	HR-ID
1	Undertake / confirm workplace risk assessment HRA (document record) and secure area	Site specific issues Worker safety Public access and unauthorised persons	3 3 3	Do inspection and review tasks and review HRA checklist Check test equipment and PPE, consult with workers involved Clear area and use appropriate barricades and signage Observe No live work policy	4 4 4	Electrical Supervisor / Worker doing the job	
2	Identify ALL energy sources and confirm isolated (8.2).	Electric Shock Personal injury	1	Follow swms3170 and swms3220 Do not work live	4	Electrical Supervisor / Worker doing the job	11
3	Undertake visual inspection to confirm installation work is complete to client's specifications. Complete installation connections to switchboard. Remove bonding leads in preparation for energising.	Minor injury	3	Refer visual inspection requirements of AS/NZS 3000 Use PPE as appropriate Ensure all circuits are suitably identified Ensure adequate lighting	4	Electrical Supervisor / Worker doing the job	
4	Check your test device/equipment for integrity and ensure is in good working order.		N/A	Before test, prove testing equipment is working correctly	N/A		
5	Test new installation and/or repairs prior to energising.		3	Refer inspection and test requirements of AS/NZS 3000 Follow Standard Working Procedures refer AS3017 Check for exposed conductors and terminate all, prior to energising Ensuring all ends are terminated and tails are secured out of reach so that no inadvertent contact can be made	4	Electrical Supervisor / Worker doing the job	
6	Replace removable switches (off) and rack-in	Minor injury	3	Confirm test equipment is operational	4	Electrical Supervisor / Worker doing the job	
7	Remove locks and out-of- service / danger tags	N/A	N/A	Locks and Danger Tags to be removed by person who placed and signed (except by supervisor in exceptional circumstances)	N/A		

DARK KHIGHT ENCINEERING		<b>ABN</b> : 776261	194992			Page 50 of 52	
9 Wenban Place, Wetherill Park, 2164	Site Supervi	sor/WHS Rep:	or/WHS Rep: Rod Griebe 0407 696 885				
Client			Section	Issue Date	Ap	proved by	
			Electrical		Rod Griebe		

V	Vork Method Description (in steps)	s) risks Level Control measures		Post Risk	Responsible Person	HR-ID	
8	Energise and test wiring, and check equipment and apparatus as operational before return to service.	Electric Shock	1	Sequence the energising and test and check, by sections (e.g. polarity) Confirm phase rotation of all 3-phase equipment Confirm operational and safe prior to handover Follow Standard Working Procedures	4	Electrical Supervisor / Worker doing the job	11
9	Tidy up installation and work areas Remove equipment from site	Minor injury	3	Use PPE as appropriate	4	Electrical Supervisor / Worker doing the job	
1	Remove signage and barriers	Minor injury	3	Use PPE as appropriate	4	Electrical Supervisor / Worker doing the job	
1	Handover installation to client	N/A	N/A	Complete certificate of compliance electrical work and other paperwork Provide relevant paperwork to client and submit to authorities, as appropriate	N/A		

- Test for de-energised every time before you touch any exposed conductors
- All PPE and test equipment shall be inspected prior to use, to ensure it is safe to use/operate and is fit for purpose
- All workers to be vigilant in relation of changes in safety conditions and workplace environment.
- All workers are authorised and expected to safely stop work and immediately notify their supervisor if a task carries an unacceptable level of risk.
- Each SWMS is developed in consultation with the workers, and monitored and reviewed by management periodically and as a result of change.

Read, understood, accepted and signed by all persons involved (refer to universal signoff Sheet 3 at back of document):

#	SURNAME	GIVEN NAME	ROLE	SIGNATURE	DATE
1					

ZOKE Š DARK KNIGHT ENGINEERING				ABN: 77626194992				
9 Wenban Place, Wetherill Park, 2164		Site Sup	Supervisor/WHS Rep: Rod Griebe 0407 696 885					Page 51 of 52
Client	Client				Section Issue Date		Approved by	
					Electrical		Rod Griebe	
		NOTES TO CONTR	ROL MEASUR	RES				
Personal Qualifications and Experience	Personnel, Du	uties and Responsib	ilities	Trainir	ng Required	to Complete W	ork	
Minimum of trades assistant or trainee /apprentice working under a qualified Supervisor, for all electrical wiring work.      Competent person to carry out da inspections of work site for hazar			1. Supervisor and employees to be trained in hazard identification, ris					hod statements,
<ol><li>No previous experience required for this activity.</li></ol>		el to maintain a tidy w rotection equipment (F times.				d current Electr nunications Autl		
3. Complete signoff to work on this task.	3. Stop work rather than accept a safety risk.  3. Appropriate industry and site induction includes the safety risk.				uction including	g NECA Red Book.		
PPE that may be required:  Long sleeved shirt, long trousers, safety footwear,			Legislation		afety Act 2011			
Sun screen (SPF30+), eye protection, gloves, ear plugs/muffs, hard hat, cap Overalls, coveralls and/or dust coat, knee pads Respirator/masks, face protection or goggles Insulated gloves and mat, insulated shields, harnesses for fall protection					afety Regulation	on 2017		
Plant/Equipment:			Standards:					
Manufacturer's recommended tools and test equip Hand tools, portable drills, appropriate mechanical Ladders, scaffold and EWP as appropriate		ment	AS/NZS 3080:2003 Telecommunications installations - Generic cabling for commercial premises (as amended 2009) and client's specifications AS/ACIF S009:2006 Installation requirements for customer cabling (Wiring Rules). AS/NZS 3012:2010 Electrical Installations - construction and demolition sites					
PPE required for minor work on asbestos conta	ining material:		NECA Red	Book - S	Safety Guide for			Communications
P1 or P2 dust mask minimum, respirator protection, disposable coveralls with fitter, hood and cuffs, boots without laces and/or boot covers, gloves where appropriate			and Data Industries 2007 AS/NZS 3000 Wiring Rules SDSs for Hazardous Substances					
Plant/Equipment required for minor work on asbestos containing material:				Codes of Practice and Guidelines				
Hand tools and ladders, paper, foam or plastic cup/s, ACM waste bags, (200 µm) HEPA filter vacuum cleaner, slow speed drill, shaving foam or gel, disposable rags, bucket of water, duct tape, sealant (non-hazardous substance) e.g. silicon or water based paint				Code of Practice Construction Work Code of Practice Managing Electrical Risks in the Workplace				
Maintenance Checks:								
Hand tools and ladders to be checked daily. All PPE and test equipment to be checked before to	ISe.							

<b>DARK KNIGHT ENGINEERING</b>		ABN: 776261	194992			Page 52 of 52
9 Wenban Place, Wetherill Park, 2164	Site Supervis	or/WHS Rep:	Rod Griebe 0407 696 885			J
Client			Section	Issue Date	App	proved by
			Electrical		Rod Griebe	

				E	lectrical		Rod Griebe					
		SWMS	Ss CONSULTATION / INSTRUCT	ION / TRAINING	RECORD							
	UNIVERSAL SIGNOFF											
	Review and evaluation of SWMSs is an ongoing process and is undertaken formally as an annual routine.											
SWN	ISs prepared and approved by:	Name:		Position:			Date: _					
	Vorker consultation, instruction, training, toolbox talks, review, acceptance record: Only persons who have completed the signoff are authorised to work on the relevant tasks covered by this document.											
I, the	I, the undersigned, acknowledge, understand and accept that:  1. the relevant HRA and above "No Live Work Policy", SWMSs and NECA Red Book have been reviewed and explained to me,  2. the contents and requirements have been explained and are clearly understood by me,  3. I shall only carry out work for which I am equipped and competent,  4. I have been consulted regarding the content of the SWMSs and the NECA Red Book,  5. I have advised my supervisor of any individual needs in relation to carrying out the work safely,  6. I will comply with the "No Live Work Policy" and SWMSs, otherwise work must stop immediately,  7. I will be vigilant regarding hazards and the suitability of the HRA and SWMS for the task at hand and implement further control measures where required, and  8. I understand that I am authorised and expected to safely stop work and immediately notify my supervisor if a task carries an unacceptable level of risk.											
#	SURNAME	GIVEN NAME	ROLE		SIGNAT	TURE		DATE				
1												
2												
3												
4												
5												
6												
7												

The list of tasks covered by this record is provided on the cover page. Signing of the individual policy and SWMS pages is only required where a change of procedure is noted.